



LED Wallpack Light

High Efficacy up to 140 lm/W and up to 85% in energy savings available in 30W-100W configurations.

APPLICATIONS

- Parking
- Education
- Health Care
- Commercial
- Automotive
- Ports
- Sports Facilities
- Automotive
- Service Center



AUTHORIZED BY:

NAME:

DATE:

DIMENSIONS & WEIGHT

PRODUCT LINE	WPD
LENGTH (cm)	23.5
WIDTH (cm)	16.45
HEIGHT (cm)	10.8
NET WEIGHT (Kg)	1.85
PCS / CARTON	6
CARTON WEIGHT (Kg)	13.5



ORDERING INFORMATION

CNX-WPD		13060	
PRODUCT TYPE	COLOR TEMPERATURE	OPTICS	WATTAGE
CNX-WPD	30 – 3000K 40 – 4000K 50 – 5000K	13060 – 130 x 60 DEGREE	030 – 30 WATTS 050 – 50 WATTS

PRODUCT SPECIFICATIONS

Construction Characteristics:

- High grade aluminum housing
- High grade thermal paste for optimal PCB to fixture cooling
- Weight: 1.85 Kg
- Powder coat finish
- IP 65 – suitable for outdoor use
- IK 10

Optical Characteristics:

- CRI (Color Rendering Index): >80
- Button or Swivel style photosensor available

Electrical Characteristics:

- Input Voltage: 120 ~ 277 VAC or 277-480 VAC, 50/60 Hz
- Power Factor: 0.9 at full load
- THD = <20%
- Operating Temperature Range: -40 ~ +50C
- Built in 6kV protection
- Optional Surge Protection: 10kV/10kA or 20kV/20kA
- 100,000 switching cycles

PRODUCT OPTIONS

FIXTURE COLOR	INPUT VOLTAGE
GRY – GREY BLK – BLACK BRZ – BRONZE SLV – SILVER CST – CUSTOM	P1 – 120~277 VAC P2 – 200~480 VAC
CONTROL	ADDITIONAL SURGE PROTECTION
CTR – CNX CONTROL DAL – 1-10V DALI ZIG – ZIGBEE MTN – MOTION PHT – PHOTOSENSOR (Button or Swivel) XXX – NO CONTROL	10K – 10KV/KA 20K – 20KV/KA (P2 ONLY) XXX – NO SURGE PROTECTION

ELECTRICAL DATA

SYSTEM WATTAGE	LUMEN OUTPUT	EFFICACY
30 WATTS	4,200 LUMENS	140 LM/W
50 WATTS	7,000 LUMENS	140 LM/W